

**PACIFIC GAS AND ELECTRIC COMPANY  
Gas Pipeline Safety OIR  
Rulemaking 11-02-019  
Data Response**

PG&E Data Request No.:	LocalUnions246-342_003-31		
PG&E File Name:	GasPipelineSafetyOIR_DR_LocalUnions246-342_003-Q31		
Request Date:	January 17, 2012	Requester DR No.:	003
Date Sent:	March 5, 2012	Requesting Party:	Plumbers/Pipe Fitters/Steamfitters Local Unions 246/342
PG&E Responder:	Ben Campbell	Requester:	Sarah Grossman-Swenson

*As used in the following questions, the terms “segment,” “pipeline segment,” and “pipeline test segment” are used synonymously, in the context of hydrostatic gas pipeline testing, to refer to the portion of a gas pipeline between the inlet and the outlet for water used in a particular hydrostatic test.*

**QUESTION 31**

With respect to each pipeline test segment upon which a hydrostatic pressure test was performed in 2010 or 2011, please state the duration of the pressurization period of the hydrostatic test.

**ANSWER 31**

Please see the RCP report for each individual test segment provided in response to LocalUnions246-342\_003-Q12 ( GasPipelineSafetyOIR\_DR\_LocalUnions246-342\_003-Q12Atch01) for this data for each test performed in 2011.

PG&E did not conduct any hydrostatic pressure tests on existing pipe in 2010.