

REVIEWOF BUREAU VERITAS (BV)
MARCH 5& MAY 15, 2014

FILM SAMPLE ASSESSMENT

REPORT 413.61-14.67

Author:

L loyd Schaefer

Senior Advising NDT Engineer

Applied Technology Services

R eviewed:

RECRIS

S tephen Simon N DT Supervisor Applied Technology Services

ATS Report #: 413.61-14.67

Rev 0



Index

Section	Content	Page
	Executive Summary	3
1.0	Badground Qual if ications	4
2.0	Approach & Results	5
3.0	Disassion	7
4.0	Conclusions & Recommendations	10
Appendix	I POSE Quantitative Analysis of BV findings for "escaped of in TO weld radiographs"	defects"
Appendix	11 Draft - B/Report 3/5/2014 - Sample review of TCI Radiographs	
Appendix	III Final BV Report 5/14/2014 - Sample review of TO Radiographs	
Appendix	V Summary of PG&E analysis of B Vassessment "non-compliant imperfection findings"	

ATS Report #: 413.61-14.67 Date of Issue: 05/30 /14

Rev 0



Executive Summary

At request the CPUC. Bureau VERITAS (B/), in January 2014, a Radiographic fil of performe d assessment/audit from a sample of 800 weld radiographic a former ROBE NOT inspections by TCI, This sample was broken down into two groups. The first group included 100 services. contractor. group included 700 welds that ROSE had that ROBE had comprehensively reviewed. The second reviewed, narrowly to this point in time, to identify the extent of condition (ECC) for is radiographic coverage. The March 5 th 2014 report from BV was reviewed by PCNE, and was found to a wide variety of factual errors. These included; fundamental mistakes, indication miss-typing & sizing errors, inconsistent, and in many cases incomprehensible nomenclature and descriptions of their concerns. The BI/ report concluded with a statistical summary which was thus erroneously derived and attempted to conclude that whether PC&E or its contractors performed that there was a 10% risk in PC&E's system for escaped defects. This report focuses B/allegations of 48 excaped defects by Radiography. It is being produced at request of the CRUC following a series of telecoms in which the CRUC agreed to consider the March 5 report (Appendix I) a "draft", pending review of R&E communication of findings against the B/ report methodology & conclusions. POSE concurs and is acting on only one of the alleged TCI escapes, a separate well repair radiograph from the group of 700 non-comprehensively finds regarding the reviewed welds. POSE balance of 47 alleged escaped defects, with present well of imagery, that all are in compliance with the 20th edition of API 1104. and were improperly cited by BV as escaped

of above described report on the BV draft of 5 March, Subsequent to the results 2014 being to the CRC. a final report was issued by Ruben Carranza of BV dated 15 May, 2014. final report Appendix III) contained nearly all of the same ROSEci ted technical errors on the part of the BV reviewers in the diraft version, as well as some new errors in in terpretation, nomendature & descriptive statistics. It was accompanied by a formal CPUC request to respond to the now 47 allegations of escaped defective welds in ROBE's system, termed also in API 1104 as imperfections, that the BV reviewers found not in compliance with API 1104 weld acceptance criteria. ROSE continues maintain that no action is required for these 47 welds, by the reasoning stated against the draft report on the same items, and based on the submitted analysis in section 2 and Appendix I of this report. Additionally the OPUC now formally requests from POSE, documentat ion of its remaining extent of condition management activities inclusive film quality and coverage, and responses to B/ recommendations. The detailed responses to these requests, as well as additional ROME findings regards the BV review process in their final report, will be addressed the discussion section of this report which has been added to complete PCSEE's response to BV's Draft and Final assessments received from the CRC. Finally, it is noted that in total BV has identified 49 separate welds with defects, a discrepancy from their summary to otals. Each one is addressed by PONE in the body of this report

ATS Report #: 413.61-14.67

Rev 0



1.0 <u>Background & Qualifications</u>

- At request of the CPUC, Bureau VERITAS (BV), in January 2014, performed a Radiographic film assessment/audit from a sample of 800 weld radiographic inspections by TCI, a former POSE NOT services contractor. This sample was broken down into two groups. The first group included 100 welds that POSE had comprehensively reviewed. The second group included 700 welds that POSE had reviewed, narrowly to this point in time, to identify the extent of condition (EOC) for issues of radiographic coverage.
- 1.2 This report documents the PCSE review and technical fact finding regards the subject March 5 2014 draft (Appendix I) as well as the final (Appendix III), May 14th 2014 BJ, reports. In these B/ attempts to show that there are film quality self-rep issues, as also previously by ROBE. Further, BV propounds that a systemic escaped defect rate of 10% exists in ROBE's pipeline system. Because the Pipeline Safety Act requires specific and prompt actions upon the revelation of weld defects, ROME took immediate action to review the report's allegations of 48 escaped defects. It was noted that this assessment was launthed with an opening meeting. However no interim reports on potential findings, or a dosing meeting were offered by B/. B/ brief on the findings of the report, informed on departure that a courtesy in advance of issuance, would be provided. This did not occur. PCBE at several points during the 2 week conducted at its ATS facility, voluntære d to hear and address any concerns, were not engaged by B/ reviewers.
- The author of this report has over 30 years of experience 1.3 in NDE. He is currently ASNT ce Level III in 5 methods, including the Radiographic Test Method. He has also been certified as Level III across a diverse array of industries, including; Saudi Aramco, Siemens, **Rolls** Boeing, Rockwell, Northrop, Honewell, , Aerojet, and SpaceX, in addition to his present as Level III for ROSE. He is an active member of the Scientific certification Advisory Boar German Federal Institute for Materials Researc hand Testing (BAM) sponsored NDE reliability working group since 1998. He has served as a member of the lowa State University, Center Non-Destructive Evaluation Industrial Advisory Board since 1995. He has authored the AST Testingrd e2dition and first or co-authored Handbook on Non-Destructive over 50 peer and symposia reviewed publications presentations. He is presently an active and voti member of the ASIME-07 standards committee for Non-Destructive Testing. A key area of his scientific studies is the modeling & measuremen to f NDE methods reliability, and germane to this report, focuses include human factors influences on probability of detection and false call causes and controls. He teathes courses in basic and advanced NDE reliability and Risk Based Life Management internationally. He is also a registered Six Sigma Black belt by the Amer Quality Engineer, and holds memberships Society for Quality, a Certified with ASNT, Dg Z ASM, AWS, ASQ and FMI.
- 1.4 This report describes the RONE approach, assessment, and conclusions regarding the Eassessment daim of 48 API 1104 code discrepancies in our pipeline welds. Additionally, in

ATS Report #: 413.61-14.67 Date of Issue: 05/30 /14

Rev 0



appendices of this report, PCNE provides quantitative substantiation for its interpretative claims that 47 of the 48 BV identified welds, are acceptable the edition theorem. ALPI 1 104. We do also note substantial errors in BVs assessment of film quality issues, but that is outside this scope of this report.

2.0 Approach & Results

2.1 Upon receipt of the now nominated draft BV assessment report, PC&E reviewed the conclusions and attempted to link to and identify the individual findings. On page 9 of the BV report a conclusion, shown below in Figure 1, indicates that there is a 10% escaped defect rate from combined sample of 800 radiographic inspections sampled.

COMBINED RESULTS

Collectively, the 800 samples yielded a 58 % Non-Compliance Rate and a 10% Defect Escape Rate.

Figure 1 - B/Combined results statement on Defect Escape Rate

- BV offers a summary (ref. pages 7 and 9 of the BV report) from each sample in support of the 10% Defect Escape Rate conclusion shown below in Figures 2 & 3. What becomes immediately clear is that neither individually, nor in summation, is BV entitled to a conclusion of an escaped defect rate of 10%.
 - DEFECT ESCAPE RATE 6 of 100 (6%) samples contained API 1104 unacceptable discontinuities that went undetected during the primary TCI Radiographic inspection.

The discontinuities detected are:

ITEM #	DEFECT DETECTED	WELD SAMPLES REJECTED
1	Internal Undercut (IU)	2
2	Incomplete Fusion (IF)	1
3	Inadequate Penetration due to Hi-Lo (IPD)	1
4	Inadequate Penetration (IP)	1
5	Elongated Slag Inclusion (ESI)	

Figure 2 - B/ calculated Defect Escape Pate for the sample of 100 weld inspections

ATS Report #: 413.61-14.67

Rev 0



 DEFECT ESCAPE RATE - 42 of 700 (6%) samples contained API 1104 unacceptable discontinuities that went undetected during the primary TCI Radiographic inspection.

ITEM#	DEFECT DETECTED	WELD SAMPLES REJECTED
1	Internal Undercut (IU)	20
2	External Undercut (EU)	1
3	Incomplete Fusion (IF)	6
4	Inadequate Penetration due to Hi-Lo (IPD)	3
5	Inadequate Penetration(IP)	5
6	Elongated Slag Inclusion (ESI)	1
7	Porosity (P)	1:
8	Burn Through (BT)	3:
9	Internal Concavity	2

Figure 3 -B/calculated Defect Escape Pate for the sample of 700 weld inspections

- 2.3 PCSE then attempted to identify the specific references to these alleged defects. Owing to pervasive unclear writing and nomenclature errors, a telecom was held with the CRUC and BV clarify which welds contained their specific findings
- 2.4 PCBE notes here that the proper form of such a rejection/finding must contain actionable information including a specific code reference and a quantified declaration in the structure of "Should be" and "Is".
- 2.5 With the BV further confirmations of the involved welds in hand, PRSE reviewed each defect escape allegation, samulariszed its own findings in Figure 4 below.

ATS Report #: 413.61-14.67

Rev 0

Cat.	Defect Type & API 1104 Code Section	BV declared defects in 100 sample	BV declared defects in 700 sample	Number & ID of those agreed by PG&E as rejectable to the applicable API-1104 code
1	Burn-Through 9.3.7		3	None
2	Int. Concavity 9.3.6	0	2	None
3	Int./Ext. UC 9.3.11	2	21	None
4	IP/IPD 931,932	2	8	One TCI escape on non-reviewed repair shot (W22R of BV item 625, TCI Env. 80-3)
5	Slag 938	1	1	None
6	Porosity 9.3.9	0	1	None
7	Inc.Fusion 9.3.4	1	6	None

Figure 4 - Summary of PC&E findings regards Escaped Defects

- 2.6 PCBE finds only one escaped defect, identified in Category 4 in Figure 4 above and is in the process of addressing the condition.
- 2.7 BV 's list of 48 defects PCBE is concerned that specific items within were draracter ized recol lection by the BV reviewers æ "extreme vere", and "critical" during telecom some of the widest comunication. POSE found degrees of interpretative errors in these item to the th 200 lition of API 1104. which were in factorptable
- 2.8 To validate PCSE's technical expert assessments of these 48 identified welds, addition supporting quantitative analyses were performed and are contained, for BV's consumption, in Appendix I. Appendix IV are now also updated to reflect the May 15 BV update which identifies a total of 4 slag conditions, none of which are found to be defects by PCSU analysis. (5/30/2014).
- 2.9 (5/21/2014)regards the single of IPD that PG&E agrees with from the d instance ROBE has determined and final BV report. that the weld in question, BV sample 625, item 80 weld 22 was in fact initially identified improper ly as a code weld, after the repa but was, determined not to be an API-1104 code weld. He nce the NDT crew was misinformed receards The NDT crew should have abanmented the requirements. this information on the reader sheet but the informationesidentis in the as built package. for clarity.

3.0 <u>Disaussion</u>

As was indicated 3.1 in the executive sumary, PC&SE has already responded in the approach and results committed **section** of this report that BV has extensive factual errors in defects" interpretations which led to the incorrect in th conclusion of "escaped (as titled or "non-compliant inperfections" version), as these SEMBLE indications were titled in the version submitted to POSE.

ATS Report #: 413.61-14.67

Rev 0

- In addition to the errors cited in Section 2 of this report, the communicated wide array of BV remaain, e.g. Item 16-3 Weld 13, BV item 371 cites in film quality disagreements missing a two shot event on the weld. Despite the clearly documented reader sheet, as well as PG&E telephonic and email communication pointing out that this is a seamweld, and not a girth weld to which the 3 shot rule is applied per code, BV includes it and all the other invalid film quality calls, despite direct evidence to the contrary. PG&E also notes that now in the final report, the number of total undercut calls has inexplicably grown from 23 to 24. The number of Internal Undercuts (IU) has decreased by 1 from 22 to 21, but the number of External Undercuts (EU) has grown by 2 to 3 (three). No explanation is given for this discrepancy, and nowhere in the text of their report is the new External Undercut cited. The identified sample number of the de-correlation is identified by PG&E as sample 5, and no claim of external undercut is made for this weld. Similarly the BV errors in its burn through assessment, where they executed a substantial forensicmiss, either applying themselves, black sharpiemagicmarker residue (see Appendix I), or failing to note it, resulting in inaccurate more dense measurements in an area of dispute.
- In attempt to understand the reasons for the unusually wide discrepancies in the interpretation of these sample TCI radiographs, PG&E reviewed its notes regards the doserved conduct of the review by BV. Most notable was that in stark contrast to industry requirements from ASTM and quantified best practices, over the course of the 2 week stay it was observed that the film review took place with the room lighting in the on condition. Measuring the ambient light levels at the viewer surfaces used by the reviewers, PG&E recorded values which are as high as 4-5 tines the ASTM limits of 3 foot candles max inturn. This was brought to the reviewer's attention, but they dismissed the need for reduced lighting as they interpreted the TCI radiographs.
- 3.4 During the course of our investigation for this report, PG&E has learned that the principal B/ for ~60-70% of the on-site dozenved as responsible film review at PG&E reviewer. physical at present an ASNT level III certificate holder in Radiography as advertised in the report of qualifications, and by his signature, and as required for this activity. The ID number sequence as well as certification dates for his ASNT methods where he is a level III certificate holder, dive penetrant and ultrasonic, indicate that he has been so certified a maximum of 5 years. This is in stark contrast to the 23 years represented in his bio. A discussion with the technical staff at ASNT has revealed that he has been only certified for 1 cycle (5 years), and for Radiography this expired in 2013 and was not renewed. ASNT prohibits the signing of documents representing ASNT level III certification when that nethod is not held.
- Neither reviewer claimed in writing, or in oral interview, any substantive experience in working with the API 1104 code. This was recognized by our external level III consultant in early communications of their findings, were B/was found to have applied ASWE code requirements for acceptance criteria, which are not applicable to the product in this review. The principal reviewers resume was reviewed on I ine (www.climbwithsummit.com/inages/charlesov.pdf), and cited technical experience as an individual contributor acquiring experience and executing

ATIS Report #: 413.61-14.67 Date of Issue: 05/30 /14

Rev 0



film reading responsibilities, pre-dates 1957, as all of the experience since that date has been in management roles and training. This experience, as well as the limited technical experience on the part of the æccord reviewer are cited Fücsök. Mül ler by et al (http://www.ndt.net/article/exndt02/429/429.htm) as being critical geps the maximized for interpretation, termed Receiver Operating Characteristic (RCC) of radiographs.

- 3.6 Despite PG&E's concerns about the preparechess, experience and credentials of the reviewers for this assessment, as well as the noted impacts to its potential reliability in its observed conduct, it is noted in a book with Title author claim from the principal reviewer; "Handbook of Testing" rd 2Edition, Nondestructive 1 a direct advoowledgement that the PG&E chosen methodology is valid. While Mr. Hellier is not the author of the majority of the book's chapters, the published drapter/section 11.3.1, while quite dated, demonstrates 2 key points regards our technical argument for acceptance, especially in the categories of; Burn through, concavity and internal / external undercut. 1. The practice of using digital radiography to measure charge in thicknesses, which all of these indications are, is a decades old practice with appious academic and cross inclustry validation. 2. It is advocated by Mr. Hellier as increasingly a code required and in all cases "an essential" means of interpreting radiographs. Despite these material facts, and a preponderance of inclustry and academic practice which validates the PG&E approach to the radiographs in question, Mr Hellier, the other BV report writers and signatories are unwilling to advnowledge that the BV final report (Appendix III , page 7) mention of the PG&E December 5, 2013 report had little to do with mechanical measurements of undercut conditions, but in fact was an explicit validation of the radiographic method of interpretation that PG&E applied. Finally on the topic of "Non-Compliant Imperfections Detected", BV cites lack of access to the welds themselves, or mechanical means to inspect them. This again improperly frames the problem which is one of interpretation, and the quantitative results obcurrented by PG&E clearly demonstrate that no code violations exist for these classes of cited "defects" or as now PG&E did communicate and declared in the final report, "Non-Compliant I mperfections". to perform measurements, or train the reviewers in the appropriate digi radiographic necesurement methods for the exaluation, but were refused in each case by the BV reviewers.
- 3.7 Finally, as to the four points of CPUC requested response:
 - 1. Review the 47 imperfections noted and provide a response on how PG&E plans to mitigate the safety risk associated with each imperfection.
 - Submit a plan to comprehensively review the entire 3755 weld population unless PG&E can
 provide substantial evidence that such a review will not decrease the risk associated with the
 welds.
 - 3. Provide a response to each of the 3 recommendations noted.
 - 4. PG&E has noted that 488 of the 3755 welds either are missing coverage, shot using 2-shot technique, or have improper 120 degree exposure. Provide a response to each weld BV identified to be either missing coverage, shot using 2-shot technique, or improper 120 degree exposure that PG&E has not included in its population of 488 welds.

ATS Report #: 413.61-14.67

Rev 0



In order to have any level of efficiency and effectiveness in this TCI recovery process, PC&E. needs to as first priority, close on issues of weld soundness and thus safety receards weld defects (draft) or non-compliant imperfections (final). The widespread and pervasive nature of errors in the final B/ report causes PC&E great concern. That said, the current status of the items is as follows: 1: The facts are clear that none of the variously 47 cited welds has non-compliant to code imperfections based on the available data. 2: The comprehensive plan to review and address the entire 3755 weld population is in execution via the funded LINL TCL EDC task . 3: As to sub 1 of the BV final report recommendations, ROME's NDE program, inclusive vendor surveillance, has been submitted and approved by the CPUC. As to sub 2 of the TO EOC task includes B/ recommendations. The LINL assessment NDT of other involved companies going back to 1961, and in the submitted and approved PCBE NDE program, all NDE ventors and their process have been audited, and all project allowed technicians have been As to sub 3 of the BV recommendations, proficiency tested & endorsed. random field observations are in place and executed to a rule based statistical sampling plan inclusive closed and maintained performance dashbooard. corrective : action 4: All agreed 2-shot short/missing coverage welds are being addressed by the LLNLTCIE OC reliability impact study task. All additional falæ call 2-shot event misses require correct ion by BV in their final requested by RGME in previous telephone and e-mail communication, in addition to being discussed in section 2 and 3 of this report.

4.0 <u>Conclusions & Reconnendation</u>

- 4.1 ROSE is not in agreement with the findings, statistical methodology, or conclusions of either the draft or final versions of the BV report: "Sample Review of TCI Radiographs". **FGXE** substant ial the B/ concerns recoarding; reviewers. their approach, andtheir analytic methodology, as is detailed in this report & summarized in Appendix IV
- the CPUC and its BV assessment 4.2 ROBE recommends that W teem appain review the technical and quantitative fact finding contained in this report, reconcile the results, and follow up with the issuance of an accurate and complete report. As desired POBE again extends the offer to host the BV assessment team if they wish to further evaluate their positions. We further recommer that the CPUC work to achieve interpretative clarity among its team by using only fully oriented, properly credentialed individuals who are experienced specifically to the requirements of API 1104.
- 4.3 POSE will await a corrected report prior to discussing the other requests and recommendations, except to re-iterate that the overall issues of film quality, limited exposure (2-shot or coverage gaps), and resultant impacts to detection reliability are being worked under contract with Lawrence Livermore Nationa. I Labs (LINL), as CPUC is all ready informed and aware.

ATS Report #: 413.61-14.67

Rev 0



Appendix I

POSE Quantitative Analysis of BV findi ngs for "escaped def ects" in TCI weld radiographs

Appendix II

March 5, 2014 BV Draft Report "Sam ple review of TOI Radiographs"

Appendix III

May 15, 2014 BV Final Report "Sample review of TOI Radiographs"

Appendix IV

PCBE Determination Sumary of BV TCI Radiographic Assessment Accuracy

ATS Report #: 413.61-14.67

Rev 0