## CGT Construction As-Built and Pressure Report Checklist

This checklist and associated as-built records shall be completed and sent to CGT within 30 calendar days of the operational date. Prepare three copies of as-built job package (red marked as-builts, pressure test reports, test charts, A-forms, facesheet, etc) and mail to Close Out Desk.

Project Name	Operative Date
District/Division	Order Number

## From Field Engineer:

Today's Date:

Mail to: Close Out Desk, Gas System Maint., 375 N. Wiget Lane, Walnut Creek, 94598

Job estimate marked up to indicate work completed, start & completion dates along with foreman's signature and initials are filled in.  As-Bulli changes to drawings and material lists are marked in red (changes on copies are highlighted).  Weld inspection stamp signed by qualified weld inspector or 100% x-ray.  Following items are clearly identified by distance from a known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate).  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3" party or weld repairs) Mnumbers (Tie-ins) T-numbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Gither Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc.) Horizontal distances are listed (as well as length installed distances are listed (with angle points, footages and fittings).  Length rested matches length installed (if not, give explanation).  Fipe and fitting specifications on rest report matches bill of materials on drawings Fressure report indicates test start and end time.	Task	Yes	No	N/A	Comments
signature and initials are filled in.  As-Built changes to drawings and material lists are marked in red (changes on copies are highlighted).  Weld inspection stamp signed by qualified weld inspector or 100% x-ray.  Following items are clearly identified by distance from a known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3 <sup>rd</sup> party or weld repairs)  Mnumbers (Tie-ins)  T-numbers (Tie-ins)  Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.)  Cher Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc)  Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested matches length installed (if not, give explanation).  Pipe and fitting specifications on test report matches bill of materials on drawings					
As-Built changes to drawings and material lists are marked in red (changes on copies are highlighted).  Weld inspection stamp signed by qualified weld inspector or 100% x-ray.  Following items are clearly identified by distance from a known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3rd party or weld repairs)  Mnumbers (Tie-ins)  T-numbers (Taps)  Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.)  Cther Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc)  Horizontal distances are listed (as well as length installed distances) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested matches length installed (if not, give explanation).  Pipe and fitting specifications on test report matches bill of materials on drawings					
marked in red (changes on copies are highlighted).  Weld inspection stamp signed by qualified weld inspector or 100% x-ray.  Following items are clearly identified by distance from a known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Rectifier, ETS, and Leak locations Rectifier, ETS, and Leak locations M-numbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Chter Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc) Horizontal distances are listed (as well as length installed distances) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and littings).  Length rested marches length installed (if not, give explanation).  Fipe and fitting specifications on rest report matches bill of materials on drawings					
Weld inspection stamp signed by qualified weld inspector or 100% x-ray.  Following items are clearly identified by distance from a known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3rd party or weld repairs) M-numbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cher Appurtenances (PCFs, repair sleeves, sav-a-valves, threadolets,etc) Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch oftested section is attached (with angle points, footages and fittings). Length rested matches length installed (if not, give explanation).  Pipe and fitting specifications on test report matches bill of materials on drawings					
inspector or 100% x-ray.  Following items are clearly identified by distance from a known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3rd party or weld repairs) M-numbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cher Appurtenances (PCFs, repair sleeves, sav-a-valves, threadolets, etc.) Hortzontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch aftested section is attached (with angle points, footages and fittings). Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Following items are clearly identified by distance from a known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3rd party or weld repairs) M-numbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Chter Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc) Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings. Sketch offested section is attached (with angle points, faotages and fittings). Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings	Weld inspection stamp signed by qualified weld				
known point on existing pipe or other landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3" party or weld repairs) M-numbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Other Appurtenances (PCFs, repair sleeves, sav-a-valves, threadolets, etc.) Hortzontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings	inspector or 100% x-ray.				
landmark/boundary that is identifiable by mapping or by a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3rd party or weld repairs) Mnumbers (Tie-ins) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cher Appurtenances (PCFs, repair sleeves, sav-a-valves, threadolets, etc.) Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested matches length installed (if not, give explanation).  Pipe and fitting specifications on test report matches bill of materials on drawings					
a GPS coordinate (sub-meter accurate):  Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3" parry or weld repairs)  M-numbers (Tie-ins)  T-numbers (Taps)  Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.)  Cther Appurtenances (PCFs, repair sleeves, sav-a-valves, threadolets,etc)  Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Changes in pipe data Rectifier, ETS, and Leak locations Repair locations (3rd party or weld repairs) Mnumbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cher Appurtenances (PCFs, repair sleeves, sav-avalves, threadolets, etc)  Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Rectifier, ETS, and Leak locations Repair locations (3rd party or weld repairs) M-numbers (Tie-ins) T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cher Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc.) Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings. Sketch of tested section is attached (with angle points, footages and fittings). Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Repair locations (3rd party or weld repairs) Minumbers (Tie-ins) Thumbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cher Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc.) Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings. Sketch of tested section is attached (with angle points, footages and fittings). Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings	Changes in pipe data				
Minumbers (Tie-ins) Tenumbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cither Appurtenances (PCFs, repair sleeves, savavalves, threadolets, etc.) Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings. Sketch of tested section is attached (with angle points, footages and fittings). Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
T-numbers (Taps) Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.) Cither Appurtenances (PCFs, repair sleeves, sav-avalves, threadolets, etc.) Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings. Sketch of tested section is attached (with angle points, footages and fittings). Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Changes in alignment and or elevation of the pipe due to offsets, rolling offsets, dog legs, etc.)  Cither Appurtenances (PCFs, repair sleeves, savavaves, threadolets, etc.)  Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
due to offsets, rolling offsets, dog legs, etc.)  Other Appurtenances (PCFs, repair sleeves, sav-avalves, threadolets, etc)  Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
valves, threadolets, etc)  Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length tested matches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Horizontal distances are listed (as well as length installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length tested matches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
installed distance) for all stationing on profile drawings and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
and detail drawings.  Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Sketch of tested section is attached (with angle points, footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
footages and fittings).  Length rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings	.,				
i.ength rested marches length installed (if not, give explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
explanation).  Pipe and fitting specifications on rest report matches bill of materials on drawings					
Pipe and fitting specifications on rest report matches bill of materials on drawings					
bill of materials on drawings	1				
Pressure report indicates test start and end time.					
ı	Pressure report indicates test start and end time.				
Pressure Report signed by Area Foreman (District	Pressure Report signed by Area Foreman (District				
Supervisor) and Test Supervisor (Field Engineer).					
Pressure report falls within pressure test limits (any	Pressure report falls within pressure test limits (any				
changes must be first authorized by Project Manager).					
Test chart indicates correct start time and date of last					
calibration.	calibration.				
All accepted and rejected x-ray reports are attached.	All accepted and rejected x-ray reports are attached.				
Main Inspection reports (A-forms) completed for each	Main Inspection reports (A-forms) completed for each				
section of pipeline exposed.					

Rev 3/1/2003