Supplemental Information for Performing AC Inspection of HPR-Type Stations

Preparation of Job Package


Print out the Service Order and HPR Atmospheric Corrosion Inspection Maps as shown in Bulletin TD-H-10B-001. If the HPR Atmospheric Corrosion Inspection Map has more than one HPR on it, only inspect the HPR's that are listed as Priority 1 or 2 in the spreadsheet. A map could contain Priority 1, 2, or 3 HPR's, and only Priority 1 and 2 HPR's are being inspected in 2010.

Print out the corresponding Service Order as shown in Bulletin TD-H-10B-001. The majority of the Service Records for found for each HPR, however, there are a number of HPR's whose Service Orders could not be located. When the link is clicked for these Service Orders, an error message will appear:



This indicates that a Service Order could not be obtained for this particular HPR. The HPR Atmospheric Corrosion Inspection Map as well as the Plat Map can be used to locate these HPR's.

Obtain Plat Maps if needed. The Plat number is listed in each Division Spreadsheet:



Supplemental Information for Performing AC Inspection of HPR-Type Stations

Identification of Atmospheric Corrosion

A challenge in Atmospheric Corrosion inspections is identifying what AC looks like.

Oxidation/Surface Rust is a common occurrence, and does not require any action. Below are examples of oxidation or surface rust:








TD-H-10B-001, Attachment 1 Supplemental Information for Performing AC Inspection of HPR-Type Stations







Atmospheric Corrosion compromises the integrity of the pipe, as it diminishes wall thickness of pipe. It consists of scaling, pitting, and/or blistering. Below are examples of atmospheric corrosion conditions that may require repairs:





TD-H-10B-001, Attachment 1 Supplemental Information for Performing AC Inspection of HPR-Type Stations





TD-H-10B-001, Attachment 1 Supplemental Information for Performing AC Inspection of HPR-Type Stations





Measuring Level of Corrosion

Once it has been determined Atmospheric Corrosion is present, the wall thickness needs to be measured. Attached is a table with Pipe sizes, wall thickness, and the maximum pit depth that is compliant.

Pipe Size	Wall Thickness	Max Pit Depth Transmission		Max Pit Depth Distribution	
1/4"	0.119		0.024		0.083
1/2"	0.147		0.029		0.103
3/4"	0.113		0.023		0.079
1"	0.133		0.027		0.093
1-1/4"	0.14		0.028		0.098
1-1/2"	0.145		0.029		0.102
2"	0.154		0.031		0.108
3"	0.216		0.043		0.151
4"	0.237		0.047		0.166
6"	0.28		0.056		0.196
8"	0.322		0.064		0.225
10"	0.365		0.073		0.256
12"	0.375		0.075		0.263
16"	0.375		0.075		0.263
18"	0.375		0.075		0.263
20"	0.375		0.075		0.263
22"	0.375		0.075		0.263
24"	0.375		0.075		0.263
26"	0.375		0.075		0.263
30"	0.375		0.075		0.263
34"	0.375		0.075		0.263
36"	0.375		0.075		0.263
42"	0.375		0.075		0.263

If the upstream (Transmission) portion of the piping has pitting with a depth equal to or greater than the above value, contact Pipeline Engineering to evaluate.

For example: On a 2" pipe, a pit depth measurement is taken, and pitting is found to be 0.036" deep. This is would indicate pitting that is deeper than the maximum according to the table above. This HPR needs to be reported to the T&R supervisor, so that Pipeline Engineering can be contacted.

If the downstream (Distribution) portion of the piping has pitting with a depth equal to or greater than the above values, corrective work beyond wax taping is needed. A GC notification needs to be created.

For example: On a 1-1/2" pipe, a pit depth measurement is taken, and pitting is found to be 0.111" deep. This would indicate pitting that is deeper than the maximum according


the table above. A GC Corrective Work Form needs to be filled out so a GC notification can be created in SAP to remediate this HPR.


If Atmospheric Corrosion is present, but the pit depths are less than the above values, recoat with wax tape.


For example: On a 4" upstream (Transmission) pipe, a pit depth measurement is taken, and pitting is found to be 0.039" deep. This would indicate pitting that is not deeper than the maximum according to the table. Recoat with wax tape. This does not warrant a GC Corrective Work Form, as this work is considered part of the inspection.

Documentation

Fill out the Stamp on each HPR Atmospheric Corrosion Inspection Map with non-erasable ink. You may use the back of the map to include additional notes. See examples below:







TD-H-10B-001, Attachment 1 Supplemental Information for Performing AC Inspection of HPR-Type Stations



POSE CONFIDENTIAL
For Internal Disease Orly
Copyright 2005 Pacific Cars & Stackle Corp.

HPR Atmospheric Corrosion Inspection
Gas System Maintenance and Technical Support
Geographic Information Services
1 inch equals 125 feet

Fill out Corrective Work Form if Expense Work is Required

If an HPR needs remediation beyond recoating with wax tape or paint, fill out a Corrective Work Form. The majority of CWF's created from HPR Atmospheric Corrosion Inspections will be priority G – Maint. Compliance. This indicates work that must be performed to ensure that our assets remain in code compliance. In rare instances a HPR may be discovered that requires immediate action, and this CWF would be filled out after the fact with a priority of A – Emergency Unsafe Condition.

Follow the guide below when filling out the CWF:

/	Corrective Work		ORDER Uso Div	<u>#:</u> stributio	n form i	f Carvi	NOTIFICATION OF THE PROPERTY O		_	
illes t	GAS DISTRIBUT	ON	use Di	Stributio	11 1011111	I Servi	ce less	than	oums	
1 People	EM DESCRIPTION: FO	· Looks	Motore N	APP etc: En	ter the Sdd	race la n	141 SHUI	ппаа	VE WAT N	ILLERKI
	For C	PA#: Ent	er CPA#		n if availab	de (e.g. C	PA 2417-B	(INSTA	ALL 2ND (SRND ROD)
2. STREET	TADDREss: Enter a	Street A	iddress					3. City	EN'	TER CITY
<u>4. Ѕтапо</u>	N NAME/NO OR CPA NO:	***	<u>5. Твен</u>	ID/BADGENO	: Mete	r number,	eto	6. Pta	T MAP NO:	***
7. Comme	ента (Long Text): <mark>*Field</mark>	s above	and Co	mments	are Impor	tant to	Correct N	otific	ation Cr	eation *
Describ	e the work required/d	one, the e	equipmer	nt & materia	ls needed (e.g. acce	ss, special	tools,	X.St). Ind	icate
specific	os (Rectifier, ETS, Ann	ual, Equi	pment ya	; CPA area	etc)to ass	ist derki	n creating	correc	t.	
	ation. Add any additio	nal comm	nents (i .e	: location or	info to hel	p identify	the equip	ment)		
☐ Corr	<u>vorkwas Identified:</u> Lective Maintenance /	□ LEA	K SURVEY			d <mark>nalinfori</mark> rance Reg	-		ATUS OF NOT NOELED	FIFICATION:
CPU(A00. B	MAJO	OR EVENT	LEM REPORT	□ PERM	_	L		MPLETED	
☐ GENE	vynaci	ed to disco oblem?	very or	MAINTENANCE	□ Езпи	indicate addition actions i				
	С Пописатіон		NOTIFICATIO		□ SO Non	RCATION	Iseded	☐ GF	В Молясалю	ON
	T-Corrective)	(Damage Claims)			L(System Deceations) Identify only 1 Notification type,		(Gas Det – Project)			
<u>12. Рион</u>	RITY: A C C G P	Promis			and the com	espondin	Priority.	PROR	<u>tv</u> : 🗆 E 🔲	L 🔲 0 🔲 R
C - BMER	GENCY UNSAFECONDITION GENCY RESTORE SERVOE	CONDITIO		AFE TORESERVOE	8 - UMBAFE (F - RESTORE	SERVICE		L = OPI	etem integri Eration Com	PLIANCE
	F. COMPLANCE EM REPAIR/IMPROVEMENT	G = MAIN	IT. COMPLAN		K = CHANGE Q = IMPROVE				LIABILITY/CAP ETEMIC PROB	
		66-Steel Ma 70-MPP PTo	n	dicate work typ	e based on w	ons L.	orros RegiStar IPP Protects		☐ 618-Sper ☐ 619-MPF	ol Leak Survey Tuspections
	verbuild Med 🔲 🥫	7 1-Suc Valu 7 2-Suc Valu	e Est 🔐	one / to be com C Work Type/M	AT Codes)	4-N	IMP Suc Value ht/Reg > 1000			Frou bles Loot
☐ 411-N	lon Recurring Proj	7 4-Reg Star 7 6-Main line	tion	600-Corre		☐ 610-N	itr/Reg<= 1000 lajor Emergend	CFH	Estimate or hours	d total minutes to complete
14. CREW	****					_	15. DURATIO		**********	MIN/H
CREW CLA			_				DURATION	(EEDED:		MIN/H
CRBN CLA	Ass: For assistance rei	erto JA_0	39 Gew G	lasses on the	Gas T&D Too	Mit	DURATION	NEEDED:		MIN/H
<u>16. Rero</u>	orted By (LAN ID): <mark>Perso</mark>	n reportir	ng the pro	oblem	<u>17. Езт. Ма</u>	TERIAL COS	<u>11:</u> \$			
<u>18. R⊜au</u>	JIRED START DATE: / /	Date	problem	found	19. Require compliant complete	se work o			erequired eit is expe	for ected to be
20. Tech or Person	місац Імерветом Ву (LAN 1 Who completed work	ID):	Foreman	21. DATE: physically co		Date work	22. Actual Actual hou	L LABOR	e Hours: to complete	Total work
23. SUP	ERVISOR									
<u>Task</u> REVW	Completed By: Supervisor Reviewed//	pproved i	by(LANIC)):			Comp. Da	<u>ite:</u>	/	
LOCAL H	HEADQUARTER CLERK									
24. Plan	т Ѕвепои/Солиту:		25. Loca	ATION/DIVISION			28. Main V	Vork Ci	ENTER:	
27. Func	тона <u>і Location:</u> GD.	*** IF FC	UNDWHIL	E DOING OTH	ER WORK - E	NTER A FL	OR EQUIPMI	ENT I D#	FROM WO	RKTICKET***
	A Corrective Work Form - Ga	c Distributio		<u> </u>						

29. Repair Codes - Crew				Select 1 O suect
		Овлест		Type/Part. (Whatis the
☐ 10 Percenter (< 100)	■ LeakStrey		<u>□</u> 11 -1	MAIN FOCUS OF THE WORK?)
☐ 10 Perceit System	☐ Motor Control Co		☐ Regenerar ☐ Gas Regu	
☐ AlliaiSystem (COD) ☐ Alliai(>1007)	☐ Diaphragm Meta		☐ Gas Regi	OBJECTS OR REPAAIR CODES USE NUMBERINSTEAD OF
□ Battery	☐ Meter - Elect Ç	ar.	☐ Rellet	CHECK MARKS.
☐ Centr Compt - Meter ☐ Centr Compt - Turb	☐ Meter – Flow Co	omp uter	□ RTU □ Sampler	
Clart	☐ Rotary Meters		☐ Separator	
☐ Cirom atograpi	☐ Turbhe Meter		■ Span	
Control Value COGI – Flame Pack	☐ Ultrasonic Meiter	TS .	☐ Scribber ☐ Suffer Ana	shows r
COGI - Mobil Units	□ Calibration		□ Tark	11744-1
□ COGI-Gas Ports	☐ Barome te r		☐ Thermal O	xidizer
☐ COGI-Gas Scope ☐ Gas Track	□ Odorometer □ Volt Meter		☐ Tower ☐ Transdice	г
□ Costroller	■ Pipe Locator		☐ Transmitte	
□ Cooler	□ Oscillator		□ Valve	
Corrosion Probe	☐ Pipe to Soll Eich	14.	□ Valit □ Variable £	rea .D.thre.
■ Deliydrafor	□ Pliot		☐ Air Switch	
☐ Detector	☐ Pipe	□ Pipe		
□ Diver □ ETS	□ PLC □ Poid		☐ Thermoco	прие
☐ Evaporator	□ PIMP			ne te r
□ fai		☐ Power Supply		d Trip
☐ Gas Fitter ☐ Differentfal Pressure Gauge		☐ Flow Recorder ☐ Electro⊪ic Press ⊪re Recorder		ot
■ Electronic Pressure Gauge	■ Mechanical Pres	■ Mechanical Pressure Recorder		Safety Value
Mechanical Pressure Garge	☐ Recip Compr - K		☐ <u>Uphole</u> Sa ☐ Drip	nte ty Value
☐ Electrical Temperature Glarge ☐ Galvanic System ——	□ Recip Compt - 1	.300	Leak Repa	III SELECT THE MAIN
	/HATIS THE SIGNIFICANT vs.tem ALLURE? gutate		Scada	ACTIVITY PERFORMED?
☐ Heater ☐ Heat Exchanger	☐ HPR Type Regu	or Starti CAUSE.?	Switch	
30. DAMAGE		1. CAUSE	' - 	32. ACTIVITY
☐ Third Party Claim	☐ 3 rd Party Damage	■ Broke i Static Lise		☐ Adjustment
☐ Third Party Damage ☐ Broke i/Damaged	☐ Depleted Arrode ☐ Dead Battery	☐ Liquids ☐ Liquids ring		☐ Calibrate ☐ Ckan
□ Cortact	□ Cracked Body	□ No Lock ip		■ Install Temporary Clamp
Afmiospheric Corrosion	□ Bad Boot or Seat	☐ Mechanical Main ro	tio i	☐ Install Nor Sip Coating
☐ Internal Corros to a☐ Debris	☐ Bad Coating ☐ Bad Cornections	☐ Value Operator ☐ Other		☐ ClearContact ☐ Add Cover
☐ High Differential	☐ Cortact	☐ 8ad Pilot		☐ Citaid Re-tire ad
□ No Display □ Exposed	☐ Corresion ☐ Bad Circuit Board	■ Bad Plate ■ No Power		☐ Raise Frame & Cover ☐ Grease & Operate
☐ klik Facility	☐ Broke ⊩ Read Dial	ad Dial 🔲 Ower Press ured		☐ Cleared Interference
☐ Interference ☐ Leak	☐ Falled Differential Test ☐ Dig in	□ Out of Range □ Street Resurfacing		☐ Change Meter ☐ Add Oil
☐ Cannot Locate	☐ Dirty Element	ent 🔲 Bad Reistate.		□ Otier
□ No Reading □ Can not 0 perate	□ Bad Fifer □ Loose Fitting	☐ Rustor Pitting		Ckar & Paint Paicr
□ Otier	■ Bad Mechailcal Fitting	anical Fitting ☐ Sithir		☐ Re-Calibrate
□ Bad Output	☐ Freezing	☐ Land Slide		☐ Re-Read
□ PavedOver □ No Power	☐ Frozen or Hard to Turn ☐ Blown Fuse			Remove Reptace
☐ Press∎re Problem	□ Goiglig	□ 8 role i Wire		☐ Repair
□ Out of Range □ Bad Reading	☐ Fire/Heat Damage ☐ Bad Hinges	☐ Bad Wrap		☐ Reset ☐ Re-Seal
□ Bad Recording	□ Inactivity			☐ Send in for Calibration
□ Broke i Stop □ Bad Differe ittal Test	□ No li k			□ Tigiter
□ Bad Differential Test □ Unsarfe Condition	☐ Falled Transition Joint ☐ No Test Lead			□ Re-Wrap □ No Action Taken
☐ Water	☐ Broke i Lid			☐ Completed

When filling out a GC Corrective Work Form for this type of work, there are many fields that will commonly have similar information, no matter the specific HPR being inspected. Here are some commonly used values:

- 1. Problem Description always begin with "HPR AC Inspection", so that the work can be easily found in SAP. Then, input the address of the HPR. For example, a Problem Description would look like "HPR AC Inspection 1101 Roosevelt Danville.
- 7. Comments (Long Text) is the reason the corrective work is needed. Input the pit depth, condition of components, or other reasons in this area. For example: "Active corrosion found on relief valve and on downstream piping. Pit depth v measured above maximum."
- 8. How was work identified always choose "CPUC Audit" for HPR AC inspections.
- 11. Always select GC Notification.
- 12. Priority generally "G = Maint. Compliance" will be selected, unless an emergency situation was encountered, corrective work was done, and the GC Corrective Work Form is being filled out after the corrective work has been completed (this will happen in rare instances when the relief is blowing or there is a severe leak found during the inspection). If emergency work is completed, select priority "A = Emergency Unsafe Condition".
- 13. Work Type select 609 if the meter being fed by the HPR is over 1000 CFH, or 610 if the meter is under 1000 CFH.
- 14. Crew Class indicate if a T&R and/or Construction crew is needed.
- 15. Duration Estimate the total man hours needed to complete the work.
- 16. Reported by enter the LAN ID of the person who inspected the HPR.
- 20. Technical Inspection By if the work has already been completed, enter the Foreman's LAN ID